

FAL 5645 Automatic L-Sealer

Robust and Value Priced

Selected by Sealed Air
Technology Engineered by Shanklin®
CT Approved Shrink Packaging Machinery



SeleCTech™ FAL 5645

Automatic L-Sealer

- Fully automatic wrapper
- Easy Load film unwind
- Machined hot knife sealing system
- Delivers strong thin package seals
- CE approved model available
- Right-to-left product flow
- Easy access electrical control panel
- Brush backed pin perforator
- Adjustable height film inverting head and take away conveyor

Quality Comes Standard

The SeleCTech™ Model FAL 5645 is the economically priced, robustly built automatic wrapping machine. The machine features gentle product feed and straight line product feed that makes it ideally suited for handling a wide variety of products. The FAL 5645 features conveyor fed automatic operation and is capable of up to 30 packs per minute. The L-seal design provides great flexibility and quick product change. The machine will accept randomly spaced product, fed either automatically or manually.

SeleCTech™ Model FAL 5645 Specifications

Sealer Size (mm) L x W Sealer Size (inches) L x W	565 x 460 22 x 17.7
Package Size (mm) L x W x H Package Size (inches) L x W x H	(100 ~ 450) x (60 ~ 350) x (5 ~ 120) (4 ~ 17.7) x (2.4 ~ 13.7) x (.2 ~ 4.7)
Floor Space (mm) L x W x H Floor Space (inches) L x W x H	1795 x 985 x 1570 70.8 x 39 x 22.5
Package Speeds	Up to 30 packs per minute
Power Requirements (by model): SLCT-FAL5645 (CE) SLCT-FAL5645	1 Phase, 230 V, 14 A, 3.5 KW, 50 HZ (with neutral) 1 Phase, 240 V, 14 A, 3.5 KW, 60 HZ (no neutral)
Pneumatic Requirements	55 PSI, 4 Kg / sq cm
Mechanical Adjustments	<ul style="list-style-type: none"> • Film roll guides • Perforator positions • Film inverting head • Product infeed table
Electrical Controls	<ul style="list-style-type: none"> • Horizontal and vertical photo eyes for accurate bag seal placement • Seal bar temperature controls • Dwell time controls for quality sealing
Other Standard Features	<ul style="list-style-type: none"> • Integrated selvage winder • Caster included • Floor stabilizers included • Emergency stops and machine reset
Optional Features	<ul style="list-style-type: none"> • Closing conveyor for short product transfer

Engineered for use with all Sealed Air Shrink Packaging Films Including Cryovac® Technology (CT) Micro-Layered Shrink Films



Shrink Packaging
100 Rogers Bridge Road
Duncan, SC 29334
866-773-4567 Fax: 864-433-2019
www.shrinkfilms.com

Our Products Protect Your Products®

Distributed by:



904, PRAGATI TOWER, 26, RAJENDRA PLACE,
New Delhi-110 008 FAX : 91-11-25751872
PH.: 25711757,25718363,25739438,25743910
Website : www.vibgyorinternational.com
E-mail : vibgyor@bol.net.in
info@vibgyorinternational.com

Corporate Offices: Sealed Air Corporation
200 Riverfront Blvd, Elmwood Park, NJ 07407 www.sealedair.com
© Reg. U.S. Pat. Off. © Sealed Air Corporation 2012. All Rights Reserved. Printed in the USA.
The "9 Dot Logo" and "Sealed Air" are registered trademarks of Sealed Air Corporation (US).